

Auto Smart Sanitizer Tunnel

www.treyfin.co.za



The Auto Smart Sanitizer Tunnel is a walk-through sanitizer unit which dispenses the correct and safe recommended dose of non-alcohol based disinfectant. This solution can be coupled with the latest smart I.O.T measuring and tracking software like:

- People counting (optional)
- Measures sanitizer level remotely (optional)
- Asset tracking and geolocation built-in (optional)

Clement Coetzee
082 801 2857 | 011 704 0284
clement@treyfin.co.za

Auto Smart Sanitizer Tunnel

R1995.00 Excl. Vat

36 Month/0% escalation

Features:

- SS 304 sqr tube frame with opaque polycarb sheet covers on side and roof
- Plug and play unit ready to be supplied with sanitiser direct in to pump unit
- SS instrument HP mist manifold with 6 off 0.2 mm sanitising mist nozzles
- Working pressure: 65~70 kgf/cm² | suction volume: 0.9~1 L/min
- 1000 psi operating pressure for optimal misting effect using the narrowest orifice nozzles
- Nickel-plated forged brass manifold resists rust and corrosion
- Special Viton seals for use with sanitisers
- Patented internal rinse cooling design to increase pump life
- Dual bearing design to lower the heat and noise level down to 75 dB
- Automatic pressure valve controls the consistency of the pump pressure
- Dual assembly with settings for minutes and seconds to set the misting intervals
- Dual analog timer has settings for minutes and seconds to set exact intervals for misting and stopping. (The shortest spray time setting: 5 seconds; the shortest stop time setting: 15 seconds)
- Beam activated entry and auto stop

Dimensions:

- 2000 mm nozzle height
- 2300 mm roof pitch
- 970 mm wide
- 2000mm long

